



**Specifications**

Model Name		QM43B	QH43B	QM50B	QH50B	QM55B	QH55B	
Display Panel	Diagonal Size (Class/Measured)	43" / 42.5"		50" / 49.5"		55" / 54.6"		
	Resolution	3840 x 2160 (16:9)		3840 x 2160 (16:9)		3840 x 2160 (16:9)		
	Brightness (Typ.)	500 nit	700 nit	500 nit	700 nit	500 nit	700 nit	
	Orientation	Landscape / Portrait		Landscape / Portrait		Landscape / Portrait		
	Antiglare	Yes (25%)		Yes (25%)		Yes (25%)		
	Contrast Ratio (Typ.)	4000:1		4000:1		4000:1		
	Type	VA		VA		VA		
	Color Gamut	92% (DCI-P3, CIE 1976)		92% (DCI-P3, CIE 1976)		92% (DCI-P3, CIE 1976)		
	Hours of Operation	24/7		24/7		24/7		
Connectivity / Sound	Input	DP 1.2 (1), HDMI 2.0 (3)		DP 1.2 (1), HDMI 2.0 (3)		DP 1.2 (1), HDMI 2.0 (3)		
		HDCP2.2		HDCP2.2		HDCP2.2		
		USB 2.0 x 2		USB 2.0 x 2		USB 2.0 x 2		
	Output	Stereo Mini Jack		Stereo Mini Jack		Stereo Mini Jack		
		Yes / Yes		Yes / Yes		Yes / Yes		
	External Control	RS232C (in/out), RJ45		RS232C (in/out), RJ45		RS232C (in/out), RJ45		
Speaker	10W, 2ch		10W, 2ch		10W, 2ch			
Mechanical Specs	Dimensions	38.09" x 21.96" x 1.9"		44.15" x 25.35" x 1.82"		48.63" x 27.87" x 1.82"		
		43.11" x 26.61" x 5.94"		49.96" x 30.87" x 5.98"		55.2" x 33.78" x 6.42"		
	Weight	22.05 lbs.	23.59 lbs.	22.05 lbs.	31.97 lbs.	39.9 lbs.	42.33 lbs.	
		29.32 lbs.	30.86 lbs.	38.8 lbs.	41.23 lbs.	52.03 lbs.	54.45 lbs.	
	VESA Mount	200 x 200		200 x 200		200 x 200		
Bezel Width	9.2mm (U/L/R), 11.2mm (B)		9.2mm (U/L/R), 11.2mm (B)		9.2mm (U/L/R), 11.2mm (B)			
Features	Internal Player	Operating System Tizen 6.5		Operating System Tizen 6.5		Operating System Tizen 6.5		
		Processor Cortex A72 1.7GHz Quad-Core CPU		Processor Cortex A72 1.7GHz Quad-Core CPU		Processor Cortex A72 1.7GHz Quad-Core CPU		
	Special	Storage (FDM) 16GB		Storage (FDM) 16GB		Storage (FDM) 16GB		
		Hardware Center IR, Temperature Sensor, Auto Level, Wi-Fi (2.4/5.0GHz dual) and BT		Hardware Center IR, Temperature Sensor, Auto Level, Wi-Fi (2.4/5.0GHz dual) and BT		Hardware Center IR, Temperature Sensor, Auto Level, Wi-Fi (2.4/5.0GHz dual) and BT		
		Software Workspace (Microsoft 365 / VMWare / RDP), Custom Home, Auto Source Switching & Recovery, Dicom Simulation Mode, Director Mode, SmartView+ (PC), Upgradeable Web Engine, Tizen Enterprise Platform, Smart Calibration, SmartView+ (mobile), Video Conference Solution, Smart Calibration, SmartView+(mobile), Video Conference Solution		Software Workspace (Microsoft 365 / VMWare / RDP), Custom Home, Auto Source Switching & Recovery, Dicom Simulation Mode, Director Mode, SmartView+ (PC), Upgradeable Web Engine, Tizen Enterprise Platform, Smart Calibration, SmartView+ (mobile), Video Conference Solution, Smart Calibration, SmartView+(mobile), Video Conference Solution		Software Workspace (Microsoft 365 / VMWare / RDP), Custom Home, Auto Source Switching & Recovery, Dicom Simulation Mode, Director Mode, SmartView+ (PC), Upgradeable Web Engine, Tizen Enterprise Platform, Smart Calibration, SmartView+ (mobile), Video Conference Solution, Smart Calibration, SmartView+(mobile), Video Conference Solution		
Certification	Safety	60950-1 / 62368-1		60950-1 / 62368-1		60950-1 / 62368-1		
	EMC	Class B		Class B		Class B		
	Environment	ENERGY STAR 8.0, EPEAT		ENERGY STAR 8.0, EPEAT		ENERGY STAR 8.0, EPEAT		
	IP Rating	IP5x		IP5x		IP5x		
Power	Power Supply	AC 100 - 240 V, 50/60 Hz		AC 100 - 240 V, 50/60 Hz		AC 100 - 240 V, 50/60 Hz		
		Max (W/h)	110	138	171	176	143	160
	Power Consumption	Typical (W/h)	79	93	91	106	108	115
Operation Condition	Temperature	32°F~104°F		32°F~104°F		32°F~104°F		
	Relative Humidity	10~80%		10~80%		10~80%		
Accessories	Included		Quick Setup Guide, Warranty Card, Power Cord, RS232C (IN) Gender, Remote Controller and Batteries		Quick Setup Guide, Warranty Card, Power Cord, RS232C (IN) Gender, Remote Controller and Batteries		Quick Setup Guide, Warranty Card, Power Cord, RS232C (IN) Gender, Remote Controller and Batteries	
	Optional	Stand	STN-L4355G		STN-L4355G		STN-L4355G	
		Mount	WMN4070SG (Landscape Only), WMN750ME		WMN4070SG (Landscape Only), WMN750ME		WMN4070SG (Landscape Only), WMN750ME	
Specialty	CML400XR		CML400XR		CML400XR			

**Learn More** [trav-adsigns.com/digital-directories](http://trav-adsigns.com/digital-directories)

**Contact Us** 256-536-4232

**Follow Us** [travadsigns](https://www.facebook.com/travadsigns)

[@travadsigns\\_inc](https://www.instagram.com/travadsigns_inc)



**Specifications**

Model Name		QM65B	QH65B	QM75B	QH75B	
Display Panel	Diagonal Size (Class/Measured)	65" / 64.5"		75" / 74.5"		
	Resolution	3840 x 2160 (16:9)		3840 x 2160 (16:9)		
	Brightness (Typ.)	500 nit	700 nit	500 nit	700 nit	
	Orientation	Landscape / Portrait		Landscape / Portrait		
	Antiglare	Yes (25%)		Yes (25%)		
	Contrast Ratio (Typ.)	4000:1		4000:1		
	Type	VA		VA		
	Color Gamut	92% (DCI-P3, CIE 1976)		92% (DCI-P3, CIE 1976)		
	Hours of Operation	24/7		24/7		
Connectivity / Sound	Input	DP 1.2 (1), HDMI 2.0 (3)		DP 1.2 (1), HDMI 2.0 (3)		
		HDCP2.2		HDCP2.2		
		USB 2.0 x 2		USB 2.0 x 2		
	Output	Stereo Mini Jack		Stereo Mini Jack		
		Yes / Yes		Yes / Yes		
	External Control	RS232C (in/out), RJ45		RS232C (in/out), RJ45		
Speaker	10W, 2ch		10W, 2ch			
Mechanical Specs	Dimensions	57.24" x 32.72" x 1.82"		66.19" x 37.8" x 1.96"		
		63.43" x 38.31" x 7.28"		73.66" x 44.37" x 8.78"		
	Weight	54.9 lbs.	58.64 lbs.	84.44 lbs.	88.85 lbs.	
		73.41 lbs.	74.96 lbs.	108.03 lbs.	112.44 lbs.	
	VESA Mount	400 x 400		400 x 400		
Bezel Width	9.2mm (U/L/R), 11.2mm (B)		11.5mm (U/L/R), 12.5mm (B)			
Features	Internal Player	Operating System		Tizen 6.5		
		Processor		Cortex A72 1.7GHz Quad-Core CPU		
		Storage (FDM)		16GB	16GB	
	Special	Hardware		Center IR, Temperature Sensor, Auto Level, Wi-Fi (2.4/5.0GHz dual) and BT		
		Software		Workspace (Microsoft 365 / VMWare / RDP), Custom Home, Auto Source Switching & Recovery, Dicom Simulation Mode, Director Mode, SmartView+ (PC), Upgradeable Web Engine, Tizen Enterprise Platform, Smart Calibration, SmartView+ (mobile), Video Conference Solution, Smart Calibration, SmartView+(mobile), Video Conference Solution		
Certification	Safety	60950-1 / 62368-1		60950-1 / 62368-1		
	EMC	Class B		Class B		
	Environment	ENERGY STAR 8.0, EPEAT		ENERGY STAR 8.0, EPEAT		
	IP Rating	IP5x		IP5x		
Power	Power Supply	AC 100 - 240 V, 50/60 Hz		AC 100 - 240 V, 50/60 Hz		
	Power Consumption	Max (W/h)	182	204	231	264
		Typical (W/h)	127	152	161	195
Operation Condition	Temperature	< 0.5W		< 0.5W		
	Relative Humidity	32°F~104°F		32°F~104°F		
Accessories	Included	Quick Setup Guide, Warranty Card, Power Cord, RS232C (IN) Gender, Remote Controller and Batteries		Quick Setup Guide, Warranty Card, Power Cord, RS232C (IN) Gender, Remote Controller and Batteries		
		No		No		
	Optional	Stand	WMN4277SF (Landscape Only), WMN750ME		WMN4277SF (Landscape Only), WMN6575SF	
		Specialty	CML450T		CML450T	

**Learn More** [trav-adsigns.com/digital-directories](http://trav-adsigns.com/digital-directories)

**Contact Us** 256-536-4232 **Follow Us** [travadsigns](https://www.facebook.com/travadsigns) [@travadsigns\\_inc](https://www.instagram.com/travadsigns_inc)